

580 Countertop Payment Terminal

PAX's \$80 is an advanced countertop POS terminal which combines innovation, durability and high performance to assure faster, more reliable transactions.

The PCI PTS 3.x approved S80 offers advanced connectivity, equipped with various communication technologies such as GPRS / 3G (WCDMA), Ethernet and PSTN. An intuitive ATM style interface and ergonomic keypad make operation easier for merchant and consumer alike.

The S80 comes with inbuilt contactless and powerful ARM11 processor, enabling support for multiple payment and value-added applications, making this countertop terminal one of the most reliable in the world.



580 Countertop Payment Terminal

FEATURES & BENEFITS



- High speed ARM 11 processor
- Large Memory Capacity
- USB & 3G connectivity
- GPRS, 3G, LAN, PSTN
- Optional built-in Contactless
 - MasterCard PayPass
 - Visa payWave

SPECIFICATIONS

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

128 x 64 pixel LCD

Keypad

10 numeric/letter keys, 8 function keys 4 ATM keys, 1 Power ON / OFF key

Printer

Thermal printer, speed: 25 lines per second Paper roll width / diameter: 58mm / 50mm

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader (optional)

MasterCard PayPass & Visa payWave 13.56MHz, ISO/IEC 14443 Type A / B, Mifare®, Felica, NFC 4 RF Indicators

Card Slots

3 SAMs

Communication

Modem: Sync. (HDLC, up to 9600bps) Asnyc. (V.92, up to 56kbps) Ethernet (optional) GPRS or 3G (WCDMA) (optional)

Peripheral Ports

1 x PINPad, 1 x RS232 1 x RS232 / Ethernet 1 x Line, 1 x mini USB (OTG)

Security

PCIPTS 3.x approved DUKPT, Master / Session, DES, 3DES ANSI / ISO9564 format 0, 1, 3 PIN ciphered key algorithm ANSIX9.9 / X 9.19 MAC algorithm

Environmental

 $0^{\circ}C$ to $50^{\circ}C$ (32°F to 122°F) operating temperature $-20^{\circ}C$ to $70^{\circ}C$ (-4°F to 158°F) storage temperature 10% to 93% relative humidity, non-condensing

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.5A Output: 8.2VDC, 3A

Physical

Length: 216mm Width: 95mm Height: 86mm

Weight

525g

Certifications

PCIPTS 3.x EMV L1 & L2 MasterCard PayPass Visa payWave EMV Contactless I.1



